

PRODUCT DATA SHEET

Royal Hydrostatic Fluid ATF



PRODUCT DESCRIPTION:

Royal Hydrostatic Fluid is an automatic transmission fluid designed specifically for use in transmissions that require Type F or MC2C33-F transmission fluid. This includes most pre-1980 Ford Automatic transmissions and many import car manufacturers' models requiring such fluid.

KEY FEATURES:

- Specialty use

CUSTOMER BENEFITS:

- Product specification and availability

APPLICATIONS:

Pre-1980 Ford and John Deer requiring J21 A

PACKAGING:

Totes and Drums

Royal Hydrostatic Fluid
ATF



Typical Properties

Royal Hydrostatic Fluid		
Product Number	202 A	Test Method
API	33.17	
Specific Gravity	0.85931	ASTM 4052
Lbs/Gal	7.156	
Density	0.85883	
Flash Point °F	197	ASTM D92
Pour Point °F	-33	ASTM D97
Color	<5.0	ASTM D1500
Viscosity@100°C cSt	7.15	ASTM D445
Viscosity@40°C cSt	34.39	ASTM D445
Viscosity Index (VI)	171	ASTM D2270

Typical Properties are typical of those obtained with normal production tolerance and do not constitute essentially a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Health and Safety:

When used for its intended application, this product is not expected to have any adverse health implications. For complete information on safe handling, as well as physical and chemical characteristics please refer to the Material Safety Data Sheet (MSDS) found on our website, www.royalmfg.com, or call 918-584-2671. Do not use this product for purposes other than its intended use. Please be responsible to the environment when disposing of used product.